



TS-888



菜園培土Vegetable Garden Banking



果園開溝Orchard Furrowing



菜園鬆土Vegetable Garden Pulverizing



作畦、開溝Bedding & Furrowing



果園開溝Orchard Furrowing

1. 模組化設計的主齒輪箱及耕耘鏈箱系統, 具有容易拆裝組合及維修簡便的優點。本機型已榮獲台灣發明專利及新型專利。
New utility model of gear box system designed, easy to install and maintenance.
2. 操縱把手可180°迴轉及五處定位點與上下高度五段式調整, 任何操作者皆適用。
Control handle easy to operate by 180° reversible handle and highness adjustable handle from five fixed position.

台灣製造、品質可靠、大順用心、農友安心
Made in Taiwan, Reliable & Stable Quality, TASOON Concern, Farmer (User's) safety.



模組化設計, 拆裝簡易
Model type design
一機多用途
Multi-feature machinery

選購配件Option Attachments

雙面犁(附輪式)Ridger

鬆土整平器Leveler



TS-888中耕培土機 鬆土、培土作業

選購加裝大順牌888型耕耘部總成, 可成為中耕培土機使用。Easy to install and added our 888 type Rotary for working ascultivator.



多功能

鬆土
作畦
開溝
培土
播種

MULTI-PURPOSES
PULVERIZING,
BEDDING
FURROWING,
BANKING
SEEDING



TS-721 雙行式雜糧播種機

選購加裝大順牌TS-721型的雙行式播種機, 可成為雙行式播種機使用。Easy to install and added our TS-721 type two-way seeder for work as seeding.

TS-566 中耕鬆土機

加裝大順牌566型阻力棒座及中耕鬆土刀組, 成為鬆土機使用。Easy to install and added our 566 type arm lock seat & tillage blade set for working as pulverizing cultivator.

規格表/SPECIFICATIONS

本表僅供參考/This list is just for references only which is subject to change without notice. 201210

規格表 / SPECIFICATIONS

本表僅供參考 / This list is for reference only, which is subject to change without notice. 2012/10

機 型 / Model	TS-888 中耕培土機 / CULTIVATOR		
尺 寸 / Dimension (cm)	L×W×H : 148×63×96	重 量 / Dry weight (kg)	86 (含耕耘刀組)
作業寬度 / Operating width (cm)	24 (8寸), 30 (1尺), 36 (1尺2寸), 47, 60	作業深度 / Operating depth (cm)	5~30
耕耘部轉速 / Rotary speed (rpm)	4檔速 / Four speed change : (1)220 (2)350 (3)400 (4)640	輪胎規格 / Tire	350-5
行走速度 / Wheel (km/h)	前進-快 / Fwd.-High : 3.96, 前進-慢 / Fwd.-Low : 2.15, 後退-快 / Rev.-High : 5.20, 後退-慢 / Rev.-Low : 2.83 (Rubber wheel / 2000rpm)		
操縱把手 / Handle control	180°迴轉, 五處定位點及五段高度調整 / 180° reversible handle and highness adjustable handle from five fixed position.		